

In order to learn which questions have been answered correctly:

1. Print these pages.
2. Answer the questions.
3. Send this assessment with the answers via:
  - a. FAX to (212) 967-3498.

Or

- b. Mail the answers to the following address:

**SYS-ED  
PO Box 1213  
New York, NY 10156**

Client contact:

<b>Name:</b>	
<b>Company:</b>	
<b>Address:</b>	
<b>City, State, Zip:</b>	
<b>Phone Number:</b>	
<b>Fax Number:</b>	
<b>E-mail:</b>	

QNO	Question	Answer
1.	<p>The list of all the CICS programs are stored in:</p> <ul style="list-style-type: none"> <li>a. PPT</li> <li>b. PCT</li> <li>c. PPP</li> <li>d. FCT</li> <li>e. TCT</li> </ul>	
2.	<p>In COBOL, all CICS statements must be terminated with a:</p> <ul style="list-style-type: none"> <li>a. RESP option.</li> <li>b. period.</li> <li>c. semi colon.</li> <li>d. EXEC CICS.</li> <li>e. None of the above.</li> </ul>	
3.	<p>The two areas that are automatically added by the translator into the LINKAGE SECTION are:</p> <ul style="list-style-type: none"> <li>a. PASSED FIELD1, PASSED FIELD2</li> <li>b. DFHBMSCA, DFHAID</li> <li>c. DFHEIBLK, DFHCOMMAREA</li> <li>d. DFHC0082, DFH0083</li> <li>e. None of the above.</li> </ul>	
4.	<p>RESP clause is used to:</p> <ul style="list-style-type: none"> <li>a. Process RESP requests.</li> <li>b. Handle exceptional conditions.</li> <li>c. Retrieve terminal data.</li> <li>d. Send terminal data.</li> <li>e. None of the above.</li> </ul>	
5.	<p>The LENGTH clause will accept a parameter of type:</p> <ul style="list-style-type: none"> <li>a. Packed decimal.</li> <li>b. Halfword binary.</li> <li>c. Float.</li> <li>d. Character.</li> <li>e. None of the above.</li> </ul>	
6.	<p>The EIB:</p> <ul style="list-style-type: none"> <li>a. Is accessible from the application program.</li> <li>b. Is addressible in your program.</li> <li>c. Contains the Tran ID that invoked this program.</li> <li>d. Contains the date and time that the task started.</li> <li>e. All of the above.</li> </ul>	
7.	<p>The HANDLE CONDITION:</p> <ul style="list-style-type: none"> <li>a. Branches to a label when an exceptional condition is detected.</li> <li>b. Branches to a label when an abend is detected.</li> <li>c. Ignores an exceptional condition.</li> <li>d. Causes an abend condition.</li> <li>e. None of the above.</li> </ul>	

QNO	Question	Answer
8.	<p>An alternative to the HANDLE CONDITION is:</p> <ul style="list-style-type: none"> <li>a. HANDLE ABEND</li> <li>b. HANDLE ERROR</li> <li>c. RESP</li> <li>d. IGNORE ABEND</li> <li>e. None of the above.</li> </ul>	
9.	<p>DFHRESP is:</p> <ul style="list-style-type: none"> <li>a. A statement that sets the default response code</li> <li>b. Is set by the INCLUDE statement.</li> <li>c. Is used to make the program more readable</li> <li>d. Cannot be used in a COBOL or ALC program.</li> <li>e. None of the above.</li> </ul>	
10.	<p>ASIS clause allows the program to:</p> <ul style="list-style-type: none"> <li>a. Run after an error is detected.</li> <li>b. Reject the PA1 and PA2 keys.</li> <li>c. Permits the program to read upper and lower case letters from the user.</li> <li>d. Sends a message to the operator.</li> <li>e. None of the above.</li> </ul>	
11.	<p>Symbolic maps contain:</p> <ul style="list-style-type: none"> <li>a. The actual terminal input.</li> <li>b. The length of each entered field.</li> <li>c. A field that allows the programmer to change the attribute of a field.</li> <li>d. Fields that allow the numeric output to be formatted.</li> <li>e. All of the above.</li> </ul>	
12.	<p>The DATAONLY option will send to a terminal:</p> <ul style="list-style-type: none"> <li>a. Only the physical map.</li> <li>b. Only the symbolic map.</li> <li>c. Both the symbolic and physical map.</li> <li>d. A clear screen.</li> <li>e. None of the above.</li> </ul>	
13.	<p>The DFHMSD macro parameter TYPE=&amp;SYSPARM will generate:</p> <ul style="list-style-type: none"> <li>a. Multiple system parameters.</li> <li>b. A symbolic and physical map.</li> <li>c. Debugging information.</li> <li>d. General terminal type.</li> <li>e. None of the above.</li> </ul>	
14.	<p>The DFHMSD macro parameter STORAGE=AUTO will generate:</p> <ul style="list-style-type: none"> <li>a. Dynamically allocates storage.</li> <li>b. Stores the memory on full word boundaries.</li> <li>c. Allocates a TIOAPFX in every symbolic map.</li> <li>d. Releases memory after every program terminates.</li> <li>e. None of the above.</li> </ul>	

QNO	Question	Answer
15.	<p>A MAPFAIL error is caused by:</p> <ul style="list-style-type: none"> <li>a. The map was not defined in the PPT.</li> <li>b. When a RECEIVE is executed and no data is read.</li> <li>c. After a data exception occurs on an input.</li> <li>d. When a SEND command is executed twice.</li> <li>e. None of the above.</li> </ul>	
16.	<p>The protection attribute:</p> <ul style="list-style-type: none"> <li>a. Turns on CICS security for all transactions.</li> <li>b. Indicates whether or not the operator can key in data into a field.</li> <li>c. Does not allow system tables to be changed.</li> <li>d. Locks the caps shift lock.</li> <li>e. None of the above.</li> </ul>	
17.	<p>Pseudo conversational programs:</p> <ul style="list-style-type: none"> <li>a. Improve the efficiency of the entire CICS region.</li> <li>b. Saves system resources when the user is typing in data.</li> <li>c. Terminates the program every time the program has to wait for user data.</li> <li>d. Uses the RETURN statement to terminate and restart the program.</li> <li>e. All of the above.</li> </ul>	
18.	<p>The first invocation of the program can be detected by:</p> <ul style="list-style-type: none"> <li>a. A flag in Working Storage.</li> <li>b. The EIB First Run flag.</li> <li>c. Checking the EIBCALEN field.</li> <li>d. Running the ADDRESS statement.</li> <li>e. None of the above.</li> </ul>	
19.	<p>The screen cursor can be given a screen position with:</p> <ul style="list-style-type: none"> <li>a. IC in the ATTRB clause.</li> <li>b. CURSOR option on a SEND.</li> <li>c. POS option on the SEND.</li> <li>d. a and b.</li> <li>e. a, b and c.</li> </ul>	
20.	<p>An abend of 0C7 would generate a:</p> <ul style="list-style-type: none"> <li>a. AICA</li> <li>b. ASRA</li> <li>c. ABM0</li> <li>d. APCT</li> <li>e. None of the above.</li> </ul>	
21.	<p>If the program in the LINK statement does not exist, the following exceptional condition would occur:</p> <ul style="list-style-type: none"> <li>a. INVREQ</li> <li>b. MAPFAIL</li> <li>c. NOTFND</li> <li>d. ABCODE</li> <li>e. None of the above.</li> </ul>	

QNO	Question	Answer
22.	A CICS deadly embrace:  a. Causes two programs to run faster. b. Would bring CICS down. c. Can always be avoided. d. Can easily be detected in the application program. e. None of the above.	
23.	TD queues are often used for:  a. printing. b. file access. c. Alternate indexes. d. Communicating with TCP/IP. e. None of the above.	
24.	The browse operation is initiated with the CICS statement:  a. READ b. BROWSE c. STARTBR d. READNEXT e. All of the above.	
25.	If a READNEXT is followed by a READPREV in a KSDS:  a. An error is initiated. b. The program reads the previous record. c. The program terminates the browse operation. d. It reads a record twice. e. None of the above.	